

Standard Fiber Patch Cord

Description:

Optical fiber jumper is widely used in FTTH,WAN,and integrated routing field.V.TORCH is a professional Manufacturer engaged in the optical products.We are committed to provide the excellent products to customers.



Feature:

- 1.Telcordia GR326,IEC, TIA/EIA Standard Compliant 100% Performance testing& excellent geometry parameter of face and core
- 2.Low insertion loss and high
- 3.ROHS compliant Return loss
- 4.Complete range

Applications:

- 1.CATV
- 2.Telecom Network
- 3.Optical Test Equipment
- 4.Wide Areas Networks
- 5.Data Processing Networks
- 6.Fiber Optic Transmission System
- 7.Testing/Measurement instruments
- 8.Fiber Distribution Frame. Fiber Optic Wall-mount& Rack-mount Cabinets

Parameter:

Name	Units	Values		
Connector	/	FC,SC,ST,LC,MU,SMA		
Mode	/	SM		MM
surface	dB	UPC	APC	PC
Insertion Loss	dB	0.15	0.2	0.15
Return loss	dB	≥55	≥65	≥35
Cable Size	mm	Φ3.0, Φ2.0, Φ0.9		
Vibration	dB	≤0.2(5~50Hz,Amplitude:1.5mm)		
TDL	dB	≤0.2(-40~85℃,21cycles)		
Fiber Type	/	SM:OS1,OS2	MM:OM1,OM2,OM3,OM4	
Storage temperature	℃	-40~+85		